

Wall Mounted Summit - R32			RAK-18PED	RAK-25PED	RAK-35PED	RAK-50PED	
Nominal Capacity (min - max)	Cooling	KW	2,00 (0,90-2,50)	2,50 (0,90-3,10)	3,50 (0,90-4,00)	5,00 (1,90-5,20)	
	Heating	KW	2,50 (0,90-3,20)	3,40 (0,90-4,40)	4,20 (0,90-5,00)	6,00 (2,20 -7,30)	
Seasonal energy rating	Cooling		A+	A+	A+	A+	
	Heating		A	A	A	A	
SEER				5.8	5.8	5.85	5.88
SCOP				3.8	3.8	3.8	3.8
EER - COP (Cooling/heating energy label)			3,45-4,03 (A/A)	3,57-3,86 (A/A)	3,21-3,82 (A/A)	3,21-3,61 (A/A)	
Sound Pressure (very low - low - med - high)	Cooling	dB(A)	21-24-33-37	22-24-33-40	25-26-36-43	28-30-40-46	
	Heating	dB(A)	19-22-33-38	20-23-34-41	26-27-36-44	25-30-39-47	
Sound Power (Eurovent data)		dB(A)		51	54	57	60
Air flow (very low - low - med - high)	Cooling	m3/h	312-350-400-440	333-370-430-510	333-400-485-600	333-450-600-700	
	Heating	m3/h	312-350-420-480	333-400-500-570	333-520-550-660	433-510-650-770	
Diameter of pipes (liquid-gas)		Inches	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	
Condensate drain diameter		mm		16	16	16	16
Remote control (standard)			Eco Control	Eco Control	Eco Control	Eco Control	
Programming			24h / 7 Day	24h / 7 Day	24h / 7 Day	24h / 7 Day	
Dimensions	Height	mm		280	280	280	280
	Width	mm		780	780	780	780
	Depth	mm		218	218	218	218
Weight		kg		7.5	7.5	7.5	8