

Multizone Wall Mounted Performance

			RAK-15QPD	RAK-18RPD	RAK-25RPD	RAK-35RPD	RAK-50RPD
Nominal Capacity (min - max)	Cooling	KW	1,50 (0,90-2,00)	2,00 (0,90-2,50)	2,50 (0,90-3,10)	3,50 (0,90-4,00)	5,00 (1,90-5,20)
	Heating	KW	2,00 (1,00-2,50)	2,50 (0,90-3,20)	3,40 (0,90-4,40)	4,20 (0,90-5,00)	6,00 (2,20 - 7,30)
Sound Pressure (very low - low - med - high)	Cooling	dB(A)	20-24-30-34	21-24-33-37	22-24-33-40	25-26-36-43	25-28-39-46
	Heating	dB(A)	20-24-32-35	19-22-33-38	20-23-34-41	26-27-36-44	27-31-39-46
Sound Power (Eurovent data)		dB(A)		47	51	54	57
Air flow (very low - low - med - high)	Cooling	m3/h	312-350-400-420	312-350-400-440	333-370-430-510	353-420-485-680	353-410-540-750
	Heating	m3/h	312-350-420-480	312-350-420-480	333-400-500-570	363-480-570-780	380-500-610-820
Diameter of pipes (liquid-gas)		Inches	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2
Condensate drain diameter		mm		16	16	16	16
Remote control (standard)			Eco Control	Eco Control	Eco Control	Eco Control	Eco Control
Dimensions	Height	mm		280	280	280	280
	Width	mm		780	780	780	780
	Depth	mm		230	230	230	230
Weight		kg		8.5	8.5	8.5	8.5

Wall mounted Shirokuma

			RAK-18QXD	RAK-25RXD	RAK-35RXD	RAK-50RXD
Nominal Capacity (min - max)	Cooling	KW	1,80 (1,00-2,50)	2,50 (0,90-3,10)	3,50 (0,90-4,00)	5,00 (1,90-5,20)
	Heating	KW	2,50 (1,10-3,20)	3,20 (0,90-4,20)	4,00 (0,90-4,80)	5,80 (2,20-7,00)
Sound Pressure (very low - low - med - high)	Cooling	dB(A)	20/25/30/36	20/27/35/43	22/29/37/45	25/31/39/47
	Heating	dB(A)	20/26/32/38	20/28/36/43	22/30/37/45	25/31/39/48
Sound Power (Eurovent data)		dB(A)		49	58	60
Air flow (very low - low - med - high)	Cooling	m3/h	300-330-430-500	300-330-510-600	320-340-520-660	350-400-580-720
	Heating	m3/h	310-360-480-600	290-370-560-680	310-380-570-720	350-420-620-800
Diameter of pipes (liquid-gas)		Inches	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2
Condensate drain diameter		mm		16	16	16
Remote control (standard)			Eco Control	Eco Control	Eco Control	Eco Control
Dimensions	Height	mm		295	295	295
	Width	mm		900	900	900
	Depth	mm		210	210	210
Weight		kg		11	11	11

Floor Mounted Shirokuma

			RAF-25RXD	RAF-35RXD	RAF-50RXD
Nominal Capacity (min - max)	Cooling	KW	2,50 (0,90-3,10)	3,50 (0,90-4,00)	5,00 (0,90-5,20)
	Heating	KW	3,40 (0,90-4,40)	4,50 (0,90-5,00)	6,00 (0,90-8,10)
Sound Pressure (very low - low - med - high)	Cooling	dB(A)	20-26-31-38	20-26-31-39	22-29-36-43
	Heating	dB(A)	20-26-31-38	20-26-31-39	22-29-36-44
Sound Power (Eurovent data)		dB(A)		55	56
Air flow (very low - low - med - high)	Cooling	m3/h	270-390-510-630	270-390-510-660	300-450-540-720
	Heating	m3/h	300-420-540-660	300-420-540-690	330-480-570-750
Diameter of pipes (liquid-gas)		Inches	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2
Condensate drain diameter		mm		16	16
Remote control (standard)			Eco Control	Eco Control	Eco Control
Dimensions	Height	mm		590	590
	Width	mm		750	750
	Depth	mm		215	215
Weight		kg		15	15

Ducts Multizone

			RAD-18QPB	RAD-25QPB	RAD-35QPB	RAD-50QPB
Nominal Capacity (min - max)	Cooling	KW	1,80 (0,90-2,50)	2,50 (0,90-3,00)	3,50 (0,90-4,00)	5,00 (0,90-5,60)
	Heating	KW	2,50 (0,90-3,20)	3,50 (0,90-5,50)	4,80 (0,90-6,60)	6,00 (0,90-7,50)
Sound Pressure (very low - low - med - high)	Cooling	dB(A)	30-33-37-41	30-33-37-41	30-33-37-41	31-35-39-43
	Heating	dB(A)	30-34-38-42	30-34-38-42	30-34-38-42	31-35-39-43
Sound Power (Eurovent data)		dB(A)		57	57	58
Air flow (very low - low - med - high)	Cooling	m3/h	400-480-560-600	400-480-560-600	400-480-570-660	400-480-570-660
	Heating	m3/h	450-520-590-650	450-520-590-650	440-510-600-720	440-510-600-720
Diameter of pipes (liquid-gas)		Inches	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2
Condensate drain diameter		mm		16	16	16
Static pressure switch in High (low, med, high)		Pa	C [42 (242)/49(274)/51(291)] H [46 (266)/52(293)/57(314)]		C [44 (243)/50(279)/58(323)] H [51 (259)/58(289)/69(340)]	
Remote control (optional)			Optional	Optional	Optional	Optional
Dimensions	Height	mm		235	235	235
	Width	mm		750	750	750
	Depth	mm		400	400	400
Weight		kg		16	16	16

Multizone Cassette

			RAI-25QPB	RAI-35QPB	RAI-50QPB
Nominal Capacity (min - max)	Cooling	KW	2,50 (0,90-3,00)	3,50 (0,90-4,00)	5,00 (0,90-5,20)
	Heating	KW	3,50 (0,90-5,00)	4,80 (0,90-6,60)	6,20 (0,90-7,60)
Sound Pressure (very low - low - med - high)	Cooling	dB(A)	28-31-34-37	30-34-38-42	32-36-40-44

Sound Power (Eurovent data)	Heating	dB(A)	29-32-35-38	30-35-39-43	32-36-40-44	
		dB(A)		50	58	58
Air flow (very low - low - med - high)	Cooling	m3/h	330-360-420-510	390-420-510-650	390-450-510-720	
	Heating	m3/h	390-420-480-550	450-480-510-660	450-510-540-720	
Diameter of pipes (liquid-gas)		pulgadas	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	
Condensate drain diameter		mm		16	16	16
Remote control (standard)			Eco Control	Eco Control	Eco Control	
Dimensions	Height	mm		285	285	285
	Width	mm		580	580	580
	Depth	mm		580	580	580
Weight		kg		20	20	20
Panel Dimensions	Height	mm		32	32	32
	Width	mm		650	650	650
	Depth	mm		650	650	650
Panel Weight		kg		4	4	4